

## KSE110XA SMEG 110CM WALLMOUNT RANGEHOOD



### POWERFUL AIR EXTRACTION

Smeg's rangehoods have been developed to optimise performance for all cooking styles and kitchen designs. We recommend using 150 mm duct pipe for peak performance.

### LED LIGHTING

Two bright, long-lasting and energy efficient LED lights clearly illuminate the cooktop below, providing maximum visibility in the kitchen no matter what type of cooking you are doing.

### 4 FAN SPEEDS

Engineered for premium performance, Smeg's rangehoods feature 3 speed settings along with an intensive function for maximum extraction, clearing the kitchen quickly of smoke and odours.

EAN 8017709280956

Dimensions	1150mmW x 1100mmH x 500mmD
Installation	Wallmount
Motor	275W
Max Airflow	702m <sup>3</sup> /hr (IEC 61591)
Noise rating	51–72 dBA (IEC 60704-2-13)
Illumination	2 x 1W LED
Speeds	3 + Intensive
Supplied Accessories	3 x Stainless steel grease filters
Optional Accessories	Charcoal filter part #FLT6
Ducting Options	Duct to atmosphere / recirculate – 150mm diameter ducting required
Power	220–240V, 50Hz 10A (3-pin plug)
Warranty	Two years parts and labour

	Extraction rate IEC 61591 [m <sup>3</sup> /h]	Noise level IEC 60704-2-13
Speed 1	297	51
Speed 2	394	58
Speed 3	513	64
Intensive speed	702	72



ID191004

## KSE110XA

SMEG 110CM WALLMOUNT RANGEHOOD



	Extraction rate IEC 61591 [m <sup>3</sup> /h]	Noise level IEC 60704-2-13
Speed 1	297	51
Speed 2	394	58
Speed 3	513	64
Intensive speed	702	72

### EAN 8017709280956

Dimensions	1150mmW x 1100mmH x 500mmD
Installation	Wallmount
Motor	275W
Max Airflow	702m <sup>3</sup> /hr (IEC 61591)
Noise rating	51–72 dBA (IEC 60704-2-13)
Illumination	2 x 1W LED
Speeds	3 + Intensive
Supplied Accessories	3 x Stainless steel grease filters
Optional Accessories	Charcoal filter part #FLT6
Ducting Options	Duct to atmosphere / recirculate — 150mm diameter ducting required
Power	220–240V, 50Hz 10A (3-pin plug)
Warranty	Two years parts and labour

